

115E-2 Ethernet Networking I/O and Gateway

Configurable and scalable multiple I/O node for industrial applications



Description

The ELPRO 115E-2 Ethernet Networking I/O and Gateway is a multiple I/O node that extends communications to sensors and actuators in local, remote, or difficult to reach locations. Designed to work with wired and wireless devices, the ELPRO 115E-2 is capable of providing IP-based I/O across sprawling industrial environments typical of industrial applications.

The 115E-2 can serve as an end node or network gateway and is scalable to thousands of nodes. Gather-scatter and block mapping technology offers the efficient use of network resources, allowing point-to-point transfer of process signal within complex monitoring and control systems. Integrated Modbus® server capability allows further I/O expansion through the use of ELPRO 115S expansion modules

The 115E-2 feature key options provides functionality for DNP3 I/O Outstation allowing for connectivity to DNP3 SCADA applications. With the combination of DNP3 and Modbus the 115E-2 also functions as a Modbus to DNP3 gateway converting legacy Modbus devices to DNP3 I/O tags.

Applications

- Water and wastewater systems
- Oil and gas production and distribution
- Pipeline monitoring and leak detection
- Mining operations infrastructure

Features

- 10/100BaseT IEEE 802.3 Ethernet communications
- Configurable digital, pulse, and analog I/O to 14-bit resolution
- Gather-scatter/block mapping and integrity checking transmissions for efficient event triggered peer-to-peer I/O
- Expandable I/O for local alarms and inputs/outputs
- Internal user configurable Web dashboard to display I/O and Diagnostics
- IO Plus Logic engine for basic controlling of I/O points
- DNP3 I/O gateway, including internal status registers
- IoT connectivity with MQTT Sparkplug B Gateway
- Modbus TCP and RTU I/O gateway
- Serial client/server/multicast Modbus TCP to RTU gateway
- Port Forwarding: Advanced network Port Forward configuration for connected Ethernet devices.
- Network diagnostics and configuration

Specifications (continued)

SPECIFICATION	DESCRIPTION
Input and Output	
Digital input	8 digital inputs (shared with outputs), 1–4 configurable as PI or PO On-state voltage: <2.1 Vdc Wetting current: 5 mA Max. I/P pulse rate DI 1/2: 50 kHz, DI 3/4: 1 kHz Max. I/P pulse width DI 1/2: 10 µsec, PI 3/4: 0.2 msec
Digital output	8 digital outputs (shared with inputs), 1–4 configurable as PI or PO Load voltage, DO max. 30 Vdc Load current, DO max. 200 mA Max O/P pulse rate, PO max. Rate 1 kHz
Analog input	4 AI (2 differential, 2 single ended) Current range: 0–24 mA Current resolution: 14 bits Accuracy (current): 0.1% Voltage input range: AI 1/2: 0–25V, AI 3/4: 0–5V Voltage resolution: 14 bits Accuracy (voltage): 0.1%
Analog output	2 AO (sourcing) Current range: 0–24 mA Current resolution: 13 bits Accuracy (current): 0.1%
Ethernet Port	
Ethernet port	10/100BaseT, RJ-45 connector, IEEE 802.3
Link activity	Link, 100BaseT via LED
Serial Port	
RS-232	EIA-562 (RJ-45 connector)
RS-485	2-pin terminal block, non-isolated
Data rate (bps)	1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200, 230400
Serial settings	7/8 data bits, stop/start/parity (configurable)
Protocols and Configuration	
System address	1 to 31-character text string
Protocols supported	TCP/IP, UDP, ARP, DHCP, DNS, ICMP, HTTP, VLAN 802.1Q, IPv6 pass through
Industrial Protocols	Gateway: Modbus RTU Master/Slave, Modbus-TCP Client/Server, DNP3 I/O, MQTT +Sparkplug Pass through: EtherNet/IP, Profinet, DNP, IEC 61850, and others
Configurable parameters	Unit details, I/O mappings, I/O parameters, Dashboard, IO Plus logic DNP3 I/O and gateway (level 2+) Modbus TCP/ RTU gateway MQTT Client +SparkplugB Embedded modbus master/slave for I/O transfer
User configuration	Network access: USB or Ethernet Remote access: over the air, Access Control List
LED Indication and Diagnostics	
LED indication	Power/OK, RS-232, RS-485, digital I/O, analog I/O status
Reported diagnostics	Connectivity information/statistics, system log file
Compliance	
EMC	FCC Part 15, EN 55022, AS 3548, CE
Hazardous area	UL/CSA Class I, Division 2; ATEX; IECEx Na IIC- PENDING
Safety	IEC 60950 (RoHS compliant)
UL	UL listed
Power Supply	
Nominal supply	10.8–30 Vdc, under/over voltage protection
Average current draw	220 mA @ 12V (idle), 110 mA @ 24V (idle)
General	
Size	5.91" x 7.09" x 1.38" (180 mm x 150 mm x 35 mm)
Housing	IP20-rated high-density thermoplastic

Ordering

SPECIFICATION	DESCRIPTION
Mounting	DIN rail
Terminal blocks	Removable, max. conductor 12 AWG 0.1 in. ² (2.5 mm ²)
Temperature rating	–40 to +140°F (–40 to +60°C)
Humidity rating	0–99% RH noncondensing
Weight	1.1 lb (0.5 kg)
Note: Specifications are subject to change.	
PRODUCT CODE	DESCRIPTION
EL-115E-2	Ethernet I/O

Accessories

PRODUCT CODE	DESCRIPTION
Interface	
915U-TCADP	T-type TCP thermocouple adapter that uses two analog inputs and two analog outputs
915U-DNP3	DNP3 I/O Outstation Feature Key Licence
FK-115E-A2	ALERT2 feature key
Cables	
ETH-CSA	Ethernet cable, 6' (1.8m), direct, RJ-45 to RJ-45
SER-RJ45	Configuration cable, RS-232 serial, DB-9 female to RJ-45
Surge Diverters	
MA15D1SI/D2SI	Power supply surge diverter, 110 Vac/15A or 240 Vac/15A
IOP32D	Signal surge diverter, 2 x 2-wire/1 x 4-wire
Power Supplies	
PS-DINAC-12DC-OK	DIN rail power supply, 100–250 Vac, 12 Vdc/2.5A
PS-DINAC-24DC-OK	DIN rail power supply, 85–264 Vac, 24 Vdc/2.5A

Note: Additional accessories are available for this product, including antennas, cables, and mounting brackets. Refer to our Web site for details.

ELPRO Technologies
29 Lathe St
Virginia, QLD 4014
Australia
www.elprotech.com
Telephone:
Global: +61 7 3352 86
USA: +1 855 443 5776

© 2023 ELPRO
All Rights Reserved
Publication No. DS_EL-115E-2

ELPRO Technologies Inc
2028 East Ben White Blvd,
#240-5656 Austin, TX 78741-6931
USA

Telephone:
USA: +1 855 443 5776

© 2023 ELPRO
All Rights Reserved
Publication No. DS_EL-115E-2

