



CONDOR

ELPRO EL-415U-1-CX BATTERY POWERED WIRELESS I/O

Condor series long-range industrial wireless I/O

DESCRIPTION

With over 35 years of Industrial Wireless expertise, the 415U-1-Cx provides asset owners with new opportunities via the smart battery and I/O monitoring technology. Designed with the Condor series long-range, high data speed radio, the 415U-1-Cx has the power and flexibility to perform reliably in sprawling harsh industrial environments.

The 415U-1-Cx easily integrates into existing 415U-2-Cx and 415U-ECx Condor Series systems feeding into IIoT networks or into Greenfield applications where critical monitoring of I/O Data is required which has not been possible before due to no power being available or too costly to integrate solar solutions.

APPLICATIONS

- **Tailings leakage** and movement detection
- **Pipeline monitoring** for Environmental protection
- **Wellhead monitoring**
- **Remote I/O** connectivity with no fixed power available
- **Sewage outfall monitoring**
- **Flood Warning**
- **Groundwater monitoring**
- **Metering** usage
- **Automatic Weather Station**
- **Flooded Roads** detection and Indication
- **Water Quality** and Environmental
- **Rainfall monitoring**

FEATURES

- Extremely low power remote I/O monitoring
- Integrated Wireless, I/O, Charger, Regulator and battery in the one water proof unit
- Supports Lithium, Lead Acid or fixed power sources
- Licenced/licence-free VHF/UHF radio transceiver
- Flexible weatherproof enclosure design allows for simple installation for cabinet or outdoor situations
- Enhanced security for both cyber and data transmission
- Two Analog inputs (4-20mA) with separate internally generated configurable 24V loop supply
- 4 Discrete inputs or Pulsed Inputs
- Flexible configuration of I/O
- Monitoring and reporting of Radio status
- SDI-12 Interface for Smart Sensors such as ice, wind, level, ground moisture and weather station applications
- Innovative power management system including integrated smart solar regulator, internal or external battery, external power options
- Direct wiring to internal junction box through M20 entry
- Tough Aluminum enclosure
- Compatible with the ELPRO Condor Series product range

Order Codes

EL-415U-1-C1	Wireless I/O Gateway	148-174Mhz
EL-415U-1-C3	Wireless I/O Gateway	340-400Mhz
EL-415U-1-C4	Wireless I/O Gateway	400-480Mhz
EL-415U-1-C5	Wireless I/O Gateway	470-520Mhz
EL-415U-1-C8	Wireless I/O Gateway	894-902Mhz
EL-415U-1-C9	Wireless I/O Gateway	828-960Mhz

SPECIFICATIONS

CONDOR II

ELPRO EL-415U-1-CX BATTERY POWERED WIRELESS I/O

Transmitter and receiver

Frequency ^a	C1 - 148-174 MHz C3 - 340-400 MHz C4 - 400-480 MHz C5 - 470-520 MHz C8 - 894-902 MHz C9 - 928-960 MHz
Transmit Power	C1 C3,4,5 C8 C9 10mW - 5W 10mW - 10W 1mW - 0.5W 1mW - 1W (10-37dBm) (10-40dBm) (0-27dBm) (0-38dBm)
Receiver sensitivity	Model C1,3,4,5 C8 C9 QPSK-FEC -116 dBm -112 dBm -112 dBm QPSK -113 dBm -109 dBm -109 dBm 16-QAM -104 dBm -100 dBm -100 dBm 64-QAM -97 dBm -93 dBm -93 dBm
Channel spacing	6.25, 12.5, 25.0 kHz (software configurable)
Typical range	50 km (62miles)
Antenna connector	N Type female

Protocols and configuration

Industrial protocols	Modbus RTU, SDI-12
User configuration	USB Type -B or RS232 Serial (9600, 8, 1, N)
Configurable parameters	Unit details, I/O mappings, I/O parameters, radio settings, Analog sample time, SDI-12 sensor sample time, SDI-12 polled sensor variables, Modbus RTU Master gateway, configurable baud, data bits, parity, stop bits.
Security	AES 256 bit

LED Indications & Diagnostics

LED Indication	Front Panel: Power/OK, Radio TX/RX, Sensor, Test mode Internal: I/O Status, Service Status, Battery Charger status
Push Buttons	Front Panel: Test Transmission Internal Boot: Test, Reset, Firmware update

Reported diagnostics

Radio diagnostics	Monitoring communications, RSSI measurements, Antenna fail, Background noise
External / Internal Inputs	Digital/pulsed/analog, solar panel/external supply voltage, battery voltage, SDI-12 data

Connections

USB Type-B	Local unit Configuration
USB Type-A	Firmware Updates, Retrieval of logged data to memory stick.
Serial	1 x RS-232 ,Configuration 1 x RS-485 Modbus RTU Master
Cable Entry	Standard M20 cable gland 5-13mm cable diameter UL/VDE, Accessory option M20 to ½" NPT Conduit Adapter
Terminal blocks	Internal wiring terminals (push connect), 0.2 - 1.5 mm ² (24 - 16 AWG), Wire Strip length 8mm (0.3")
Antenna connector	N Type female

Operation

Modes—topology	Remote Unit Type.
----------------	-------------------

Input and output

Discrete input/output	4 Digital Inputs configurable as on/off or DI1-3 pulse inputs
Analog inputs	2 differential analog inputs configurable 0-20mA (under/over range), 16 bits resolution
Analog loop power	Analog: 24Vdc, max 50mA SDI-12: 12Vdc, max 500mA
SDI-12 (V1.4)	Maximum of 5 configured variables total M or R command / CRC configurable
Heater Output	Open Collector output (active close to ground) ON @ -0°C OFF @ 2°C, 30Vdc/2A max

Compliance

RF (radio)	Australia: RCM, Europe: CE/RED, USA: FCC, Canada: IC RF: FCC CFR47 Part 90; IC RSS 119; EN 300 113; EN 300 220; AS/ NZS4295; AS/ NZS4268
EMC	FCC CFR47 Part 15; EN 301 489-3; EN 301 489-5
Safety	EN/IEC/UL 62368
Hazardous area	Class I, Division 2

Power supply

Nominal supply	17-30 Vdc, undervoltage/overvoltage protection External Battery 11-15Vdc, under/ over voltage protection
Battery charger	Lithium Iron Phosphate (LFP): Internal rechargeable Lead Acid (Pb): 12V Battery Externally connected
Battery Charger or Solar Regulator	External power supply/MPPT solar panel charges internal lithium (LFP) or external battery Up to 2A charge optimized for 5-30W panel Automatic temperature compensation/protection
Idle current draw	Field Station 100µA
Transmit current draw	2.5A @ 13.8Vdc (10W RF) 1.2A @ 24Vdc (10W RF)
Battery Life @ 5W RF Power, 2 x Digital Inputs 60min Updates	Non Rechargeable Lithium (LiP): 2 years
Battery Life @ 5W RF Power, 1 x Analog Inputs 60min Sample time.	Non Rechargeable Lithium (LiP): 7.2 Months.

General

Size (H x W x D)	190 x 197x 98 mm (7.5"x 7.8"x 3.8")
Housing	Aluminum cast enclosure with removable door. IP66 rated
Mounting	Panel mount standard (DINA rail, pole or solar mount options)
Temperature rating	External supply -40 to 70°C (-40 to 158°F) LFP rechargeable battery -20 to 60°C (-4 to 140°F)
Humidity rating	0-99% RH non condensing
Weight	1.8 kg (4.0 lb) - not including internal battery
Altitude	0-3000m (0-10000ft)
Polution Degree	4

^a Available RF power and frequency may vary depending on country and model selected. Please confirm with local regulatory body.

Specifications subject to change

CONTACT

Australia

ELPRO Technologies
29 Lathe Street
Virginia QLD 4014
T +61 7 3352 8600
E sales@elprotech.com
W elprotech.com

USA

ELPRO Technologies Inc
2028 East Ben White Boulevard
#240-5656 Austin, TX 78741-6931
T +1 855 443 5776
E sales@elprotech.com
W elprotech.com

HOW TO ORDER

Simply send us an email at sales@elprotech.com, contact your local distributor, or phone **+61 7 3352 8600**

An **envirada** group company