

# PS-WW-XP-24DC Power Supply

Plug-in power supply for ELPRO products



## Description

The PS-WW-XP-24DC Power Supply provides 24 Vdc, suitable for powering ELPRO products. The product includes Australian and International mains power adaptors for use in other countries.

This power supply is not suitable for use with 5W-licensed units. Confirm your power supply requirements before use.

The PS-WW-XP-24DC Power Supply is terminated with a standard 0.08" (2.1 mm) DC plug, suitable for use with ELPRO demonstration kits. Remove the DC plug before making a bare wire connection to ELPRO product terminal blocks. (This type of installation should be performed by a professional electrician or systems integrator.)

## Specifications

SPECIFICATION	DESCRIPTION
<b>Input and output</b>	
Input	100–240 Vac, 50–60 Hz/120–370 Vdc <sup>a b</sup>
Output	24 Vdc, 1.25A <sup>a</sup>
Terminations	0.08" (2.1 mm) DC plug
<b>General</b>	
Temperature	0–104°F (0–40°C)
Humidity	15–95% noncondensing
<b>Compliance</b>	
EMC	CE, C-Tick
Safety	UL, CUL, TUV, GS, SAA, CE, CB, UL60950

**Note:** Specifications are subject to change.

<sup>a</sup> Worldwide operation

<sup>b</sup> Comes with AU & International power adapters

## Ordering

PRODUCT CODE	DESCRIPTION
PS-WW-XP-24DC	Plug pack universal input, 24 Vdc/1.25A output

## Product Compatibility

See your product data sheet for information about compatibility of the PS-WW-XP-24DC Power Supply with your application.

ELPRO Technologies  
29 Lathe St  
Virginia, QLD 4014  
Australia  
[www.elprotech.com](http://www.elprotech.com)

Telephone:  
Global:+61 7 3352 86  
USA: +1 855 443 5776

© 2024 ELPRO  
All Rights Reserved

ELPRO Technologies Inc  
2028 East Ben White Blvd,  
#240-5656 Austin, TX 78741-6931  
USA

Telephone:  
USA: +1 855 443 5776

© 2024 ELPRO  
All Rights Reserved

ELPRO Technologies is a registered trademark.

All other trademarks are property of their respective owners.

