



**ACCESSORIES** +  
**ANTENNA ACCESSORIES**  
**COAX CABLE KITS**

Pre-terminated coax cables for easy commissioning

## CC CABLES

The CC Cable Kits come in a variety of lengths and coax connectors.

They are all manufactured with RG-58 low-loss coaxial cable and have a N Type Male coax connector on one end and either an SMA, BNC or another N Type connector on the other end, depending on the version.

This cable delivers an easy integration with ELPRO products and/or other accessories such the in-line surge arrestors..



## SPECIFICATIONS

Parameters	CC3-XXX	CC5-XXX	CC10-XXX	CC20-XXX	CC5-RG213
Cable	RG-58 low-loss (Belden (9006)				RG213
Connector #1	N-Type-Male				
Connector #2	Connector will vary (N Type, SMA or BNC) depending on cable type.				
SMA Male	✓	✓	✓	✓	
N-Type Male	✓	✓	✓	✓	✓
BNC Male			✓	✓	
Length	3m (9.8')	5m (16.4')	10m (32.8')	20m (66')	5m (16.4')
<b>Losses</b>					
150 MHz	0.6 dB	0.9 dB	1.5 dB	2.8 dB	0.5 dB
450 MHz	0.9 dB	1.4 dB	2.7 dB	5.1 dB	0.7 dB
900 MHz	1.1 dB	1.7 dB	3.5 dB	7.0 dB	1.1 dB
2.4 GHz	2.0 dB	3.4 dB	6.8 dB	13.6 dB	2.0 dB
5G Hz	3.0 dB	5.0 dB	9.9 dB	19.8 dB	3.7 dB
<b>Order Codes</b>					
CC3-SMA	Cellfoil Coaxial Cable: 3m (9.8') long, N-type (male) to SMA (male)				
CC3-N	Cellfoil Coaxial Cable: 3m (9.8') long, N-type (male) to N-Type (male)				
CC5-SMA	Cellfoil Coaxial Cable: 5m (16.4) long, N-type (male) to SMA(male)				
CC5-N	Cellfoil Coaxial Cable: 5m (16.4) long, N-type (male) to N-Type (male)				
CC10-SMA	Cellfoil Coaxial Cable: 10m (32.8') long, N-type (male) to SMA (male)				
CC10-N	Cellfoil Coaxial Cable: 10m (32.8') long, N-type (male) to N-Type (male)				
CC10-BNC	Cellfoil Coaxial Cable: 10m (32.8') long, N-type (male) to BNC (male)				
CC20-SMA	Cellfoil Coaxial Cable: 20m (66') long, N-type (male) to SMA (male)				
CC20-N	Cellfoil Coaxial Cable: 20m (66') long, N-type (male) to N-Type (male)				
CC20-BNC	Cellfoil Coaxial Cable: 20m (66') long, N-type (male) to SMA (male)				
CC5-RG213	RG213 Coaxial Cable: 5m (16.4') long, N-type (male) to N (male)				

**Note: Specifications are subject to change.**

## CONTACT

### Australia

ELPRO Technologies

29 Lathe Street

Virginia QLD 4014

**T** +61 7 3352 8600

**E** [sales@elprotech.com](mailto:sales@elprotech.com)

**W** [elprotech.com](http://elprotech.com)

### USA

ELPRO Technologies Inc

2028 East Ben White Boulevard

#240-5656 Austin, TX 78741-6931

**T** +1 855 443 5776

**E** [sales@elprotech.com](mailto:sales@elprotech.com)

**W** [elprotech.com](http://elprotech.com)

## HOW TO ORDER

Simply send us an email at

[sales@elprotech.com](mailto:sales@elprotech.com), contact your local distributor, or phone **+61 7 3352 8600**