ELPRO Technologies

QUANTUM

ELPRO EL-QC-X-XXX
QUANTUM CLASSIC

Industrial Wireless Controller,
I/O Gateway & more!

DESCRIPTION

The EL-QC-XXXXX Quantum Classic is the Remote I/O networking workhorse within the ELPRO Technologies Quantum Ecosystem, designed to provide secure, scalable, and intelligent connectivity across industrial and critical infrastructure applications.

Combining industrial I/O gateway, protocol conversion, and multi-technology wireless communications functionality, Quantum Classic enables seamless integration between field devices, SCADA systems, OT networks, enterprise infrastructure, and cloud-based platforms.

Supporting point-to-point, point-to-multipoint, and mesh network topologies, the platform is suited to distributed IIoT, Edge (“Fog”), and Cloud architectures.

Quantum Classic supports a wide range of industrial protocols including Modbus RTU/TCP, DNP3, MQTT Sparkplug B, OPC-UA, serial tunnelling, and LoRaWAN integration (model dependent).

The platform supports a broad range of industrial communication technologies, including:

- 2.4GHz & 5GHz Industrial Wi-Fi
- Licensed UHF/VHF narrowband radios
- Unlicensed 900MHz FHSS and fixed frequency 869MHz
- Cellular LTE and 5G
- LoRaWAN 868MHz and 900MHz gateway functionality

Selected models support dual-radio and hybrid communication architectures for increased redundancy and network flexibility.

Built on an industrial Linux platform, Quantum Classic includes embedded Node-RED functionality for edge processing, workflow automation, protocol translation, and cloud integration.

FEATURES

Dual Core 1.2GHz Processor Arm® Cortex®-A53, 2GB RAM Memory, 8GB Flash Memory.

Inbuilt short range 2.4GHz or 5Ghz selectable WiFi, compatible with our existing 245U-E and 215U-2 wireless modems & I/O products.

Integrated digital, analog, and pulse I/O, expandable I/O for extra local alarms and inputs/outputs

Support for RS485 MTL HART MUX communications

HART Multi-drop interface on all analog input/outputs (upcoming release)

ELPRO ProMesh(TM) redundant path selection and network formation

Gather-scatter/block mapping and integrity checking transmissions for efficient event triggered peer-to peer I/O

Modbus TCP/UDP Client and/or Server & Modbus RTU I/O gateway

DNP3 I/O gateway, including internal status registers

MQTT and SparkplugB Gateway IoT Connectivity

LoRa Gateway & Application Server (Model Specific)

Diagnostic Data & Event Logging capabilities

IO Plus Logic engine for compatibility with existing Condor implementations.

User configurable Internal Web based Dashboard to display I/O and Diagnostics

Node-Red, Flow-based Programming environment with configurable Control, Actions and User Dashboards.

Over-the-air network diagnostics and configuration

APPLICATIONS

- Industrial automation and process control
- SCADA and telemetry infrastructure
- Oil & gas pipeline monitoring and control
- Water and wastewater treatment systems
- Renewable energy and power distribution networks
- Smart utility and critical infrastructure networks
- Remote equipment diagnostics and predictive maintenance
- Tank, pump, pressure, and valve monitoring
- Environmental and weather monitoring systems
- Mining, rail, and transport infrastructure
- Distributed alarm and safety systems
- Industrial protocol conversion and data integration
- IIoT and cloud connectivity applications
- Remote site communications and automation
- Hybrid wireless network infrastructure

FEATURES (ext)

System Firmware Upgrade: Centralised management of firmware patch updates and automated over the air deployment

Centralised & Automated over the air management/rotation of system encryption keys

Over the air Transparent Layer 2 Wireless LAN (IEEE802.11)

Supports multiple data rates simultaneously for high performance over short and long communication links

Standard Ethernet bridge to allow modem function for external Ethernet host devices (full L2/L3 network support)

Secure data protection using advanced Encryption methods

Port Forwarding (NAT): Advanced network Port Forward, configuration for connected Ethernet devices.

Radio Access Control: Extension of existing MAC/IP filtering to include deny/allow-list filtering based on MAC or Serial number.

Upcoming models to include additional communications interfaces, some multiple to provide communication with a range of Radio and Cellular frequency bands and communication mediums.

Base Communications (Ethernet & Low Power WiFi)	
Technology	IEEE 802.11ac Wave 2 1x1 WiFi
Frequency bands[d]	2.412–2.484 GHz / 5.150–5.895 GHz
Transmit power	2.4Ghz - 18dBm (62mW)/5Ghz - 15dBm (32mW)
Modulation	Orthogonal Frequency Division Multiplexing (OFDM)
Receiver sensitivity	2.4Ghz: –92 dBm@7.2Mbps, -62 dBm@200 Mbps 5Ghz: –91 dBm@7.2Mbps, -59 dBm@433 Mbps
Channel spacing	2.4Ghz (13, overlapping 20Mhz channels) / 5Ghz (13, 20Mhz channels). 20/40/80 MHz channel size support
Supported Data Rates	2.4Gh (1 –200 Mbps)/ 5Ghz (6 - 433 Mbps) “Auto Mode” selects fastest rate possible relative to RSSI and Channel Width.
Typical range	Both 2.4Ghz & 5Ghz - 250m (820ft) LoS
Antenna connector	1 x female SMA, standard polarity
EMC	FCC Part 15; EN 301 489-17; AS/NZS CISPR22
RF (radio)	EN 300 328; EN 301 893; FCC Part 15; RSS 210
Basic Comms	**Primary/Secondard Communication Options**
Ethernet, Short range 2.4Ghz & 5Ghz WiFi	Narrow-band Long range UHF/VHF radio, 900MHz unlicensed FHSS, unlicensed 869MHz, Cellular, LoRaWan,

Communications (Longe Range UHF/VHF Radio)		
Technology	VHF / UHF Radio	
Frequency bands[e]	148-174 MHz, 340-400 MHz, 400-480 MHz, 470-520 MHz	
Transmit power-average[e]		
QPSK	4 W (+36 dBm)	
16/64QAM	2.5 W (+34 dBm)	
2-FSK, 4-FSK	10 W (+40 dBm)	
Modulation	QPSK, 16-QAM, 64-QAM, 2-FSK or 4-FSK (compatibility mode)	
Receiver sensitivity 6.25/12.5/25 kHz	QPSK-FEC	–116 dBm
	QPSK	–113 dBm
	16-QAM	–104 dBm
	64-QAM	–97 dBm
	2-FSK	–110 dBm
	4-FSK	–102 dBm
Channel spacing	6.25, 12.5, 25.0 kHz (software configurable)	

Data Rates - Raw/ no compression. Data compression can provide up to 50% improvment, depending on data content.

Encoding	**Channel 6.25khz**	**12.5Khz**	**25Khz**
QPSK-FEC	4 kbps	8 kbps	16 kbps
QPSK	8 kbps	16 kbps	32 kbps
16-QAM	16 kbps	32 kbps	64 kbps
64-QAM	24 kbps	48 kbps	96 kbps
2-FSK		4.8 kbps	9.6 kbps
4-FSK		9.6 kbps	19.2 kbps

Typical range	100 km (62 miles) at 4 W 16 km (10 miles) at 0.5 W
Antenna connector	SMA female, standard polarity
EMC	FCC CFR47 Part 15; EN 301 489-3; EN 301 489-5
RF (radio)	FCC CFR47 Part 90; IC RSS 119; EN 300 113; EN 300 220-2; AS/NZS4295; AS/NZS4268

Communications (Unlicenced 869Mhz Fixed & 900Mhz FHSS)	
Transmission	900Mhz Frequency Hopping Spread Spectrum (FHSS) [ab] 869Mhz Single frequency [c]
Frequency bands	902–928 MHz [ab], 869.525 MHz [c], 869.875 MHz [c]
Transmit power	1W (+30 dBm)[ab] , 5mW [c] (5dBm) or 500mW [c] (27dBm)
Modulation	Frequency shift keying (FSK)
Receiver sensitivity	–109 dBm @ 19.2 kbps (3% FER) [ab] –109 dBm @ 14.4 kbps (3% FER) [c]
Channel spacing	50 x 250 kHz [ab], single 250 kHz [c]
Data Rates	19.2–115.2 kbps [ab], 14.4–76.8 kbps [c]
Typical range	32 km (20 miles) @ 4W EIRP [a] 15 km (9.3 miles) @ 1W EIRP [b] 10 km (6 miles) @ 500 mW EIRP [c]
Antenna connector	female SMA standard polarity
EMC	FCC Part 15; EN 301 489-3; CISPR 32
RF (radio)	FCC Part 15.247; EN 300 220-2; AS 4268.2; RFS29 NZ
Communications (LoraWAN EU868, US915, AS923, AU915, KR920, IN865)	
Technology	RAK2287 LPWAN Concentrator Module
Frequency bands	Supports global license-free frequency bands EU868 = 863-870Mhz, Europe US915 = 902-928MHz, Nth & Central America AU915 = 915-928MHz, Australia, NZ, Sth America IN865 = 865-867Mhz, India AS923 = 923-925Mhz, Asia KR920 = 920-923Mhz, Sth Korea
Transmit power	Tx power up to 27 dBm
Modulation	Chirp Spread Spectrum (CSS)
Receiver sensitivity	Rx sensitivity down to -139 dBm @ SF12, BW 125 kHz
Channel spacing	8 x 8 channels LoRa packet detectors, 8 x SF5-SF12 LoRa demodulators, 8 x SF5-SF10 LoRa demodulators, one 125/250/500 kHz high-speed LoRa demodulator and one (G) FSK demodulator
Supported Data Rates	125 kHz, 250 kHz or 500 kHz, depending on the region or the frequency plan
GPS	Built in ZOE-M8Q GPS module
Typical range	10 km in rural areas and up to 3 km in dense urban areas depending on band and configuration.
Antenna connector	1 x female SMA, standard polarity
EMC	FCC Part 15; EN 301 489-3; CISPR 32
RF (radio)	FCC Part 15.247; EN 300 220-2; AS 4268.2; RFS29 NZ
Communications (Cellular LTE)	
Technology	3G/4G/5G Connectivity including Band 28
Frequency bands[d]	Worldwide LTE, UMTS/HSPA+ and GSM/GPRS/EDGE coverage
Region	Australia, Asia, New Zealand, South America North America, EMEA, Thailand
Cell Category	Cat4
Band (LTE)	B1, B2, B3, B4, B5, B7, B8, B8_US, B9, B12, B13, B14, B18, B19, B20, B25, B26, B28
Band (WCDMA)	B1, B2, B4, B5, B6, B8, B19
Band (GSM/EDGE)	B2, B3, B5, B8
Carrier	Telstra, Optus, Vodaphone, Verizon, AT&T, T-Mobile, FirstNet, US Cellular, Rogers, Telus, Vodaphone, O2, Three, Orange, Deutsche Telecom
LED Indications & Diagnostics	
LED Indication	Power/OK, Radio Primary & Secondary (if fitted), TX/RX/Link, RS-232, RS-485, LAN/100/1000, I/O status

Protocols and Configuration	
System address	ESSID; 1 to 31-character text string
Networking protocols	TCP/IP, UDP, ARP, DHCP, DNS, ICMP, HTTP, VLAN 802.1Q, IPv6 pass through
Industrial protocols	Gateway: MQTT Client & Broker, SparkplugB, Modbus RTU, Modbus TCP/UDP, DNP3 I/O, HART to Modbus, ELPRO WIB compatibility Ethernet Pass through: EtherNet/IP, PROFIBUS DP, PROFINET, DNP, IEC 61850, and others
Configurable parameters	Unit details, I/O mappings, I/O parameters, radio settings, Dashboard, IO Plus logic, DNP3 I/O and gateway (level 2+), Modbus TCP/UDP/RTU gateway Embedded Modbus master/slave for I/O transfer Frequency agility parameters for automatic selection of radio paths, prioritization of traffic flows, bandwidth efficiency features, bandwidth utilization, redundancy, routing, bridging, VLAN
User configuration	Network access: USB or Ethernet Remote access: over the air
Node Red	Flow-based, Web page accessable development tool for visual programming
Security	WPA2-PSK, AES 256 bit, multilevel password protected configuration, Access Control List
IP filtering	IP address, MAC address, ARP filtering whitelist/blacklist & serial number, Access Control List
Compliance (EMC & RF, check communication option Specs)	
Safety	UL Listed (RoHS Compliant), EN/IEC 62368
Hazardous area	UL Class I, Division 2, ATEX Zone 2; IECEx ec IIC
Connections	
LAN	2 x 100Mb auto-MDIX RJ-45
Serial	1 x RS-232, 1 x RS-485, 300–12Mb/s baud including Profibus rates, SDI-12 Serial over IP modem support
USB	1 x Type C 1 x Type A
DVI	Video Output 1080p
SD-Card	1 x Micro SD-Card
Input and output	
Discrete input/output	8 digital I/O (1-4 configurable as PI or PO) Inputs: Contact to GND, 2 Vdc, Wetting 5 mA Outputs: open Drain to 30VDC, 400mA max Max. I/P pulse rate – 10 KHz Min. I/P pulse width – 40 µs
High current output	One digital output N/O (Form A) contact to 60Vdc/30Vac 5Amp Output current (continuous) 30A start current (Peak 100msec)
Analog inputs	6 AI (selectable for Voltage/current) Dip Switch Selectable for mA or voltage Each pair configurable for differential input Accuracy: 0.1% At ambient temp Resolution 12-bit ADC Analog In support HART Protocol FSK Physical layer
Analog output	2 AO (sourcing) Current range: 0.5mA - 24 mA Current resolution: 13 bits Accuracy (current): 0.1% Analog Out support HART Protocol FSK Physical layer
Analog loop power	+24 Vdc output provided to power loop devices Max. Current 200 mA – current limited
Expansion	Compatible with 115S series Modbus I/O modules

SPECIFICATIONS

QUANTUM

ELPRO EL-QC-X-XXX
QUANTUM CLASSIC

Power supply	
Main supply	9-50 Vdc, under voltage / over voltage protection, Replaceable Fuse Supply max 60W (including battery charging) Support Solar panel up to 200W for battery charging
Battery Supply	12V PbSO4 (Lead-acid) or LiFePO4 (Lithium Iron Phosphate) backup battery. Battery charging from 9V Main Supply. 12V/24V Solar Panel up to 200W. Charge up to 5A / 60W from main supply Low Temp Charge disable (Selectable -20 or 0°C (-4 or 32°F) Over/Under Voltage protection with replaceable fuse.
Average current draw	500 mA at 13.8 V (idle), 300 mA at 24 V (idle)

General	
Processor Core	2 x Cortex®-A53 1.2Ghz, 2G RAM Memory, 8G Flash Memory.
Dimensions	180 x 150 x 40mm (HxDxW), 6.70 x 5.9 x 1.6 inches
Weight	0.8 kg (1.8 lb)
Housing	Die-cast, Powder-coated aluminum and high-impact Plastic, Poly Carbonate/ABS Blend, IP20 rated
Terminal blocks	Front - Removable, max. 16 AWG (1.5mm²) Bottom - Removable, max. 12 AWG (4mm²)
Mounting	DIN rail
Temperature rating	-40 to +70°C (-40 to +158°F)
Humidity rating	0-90% RH non-condensing
Altitude	0-2000m / 6500ft (Performance derating applies above this altitude)

[a] Configured for US.
[b] Configured for Australia, Brazil
[c] 869 MHz ISM band (Europe)
[d] Specific parameters may vary depending on Country, Region, Model & Configuration
[e] Available RF power and frequency may vary depending on country and model

Specifications subject to change

Main Model Order Codes	
EL-QC	Base Model, Local Wifi (2.4/5Ghz), IO, Ethernet, Serial
EL-QC-LW8	Base EL-QC & LoraWAN868, IO, Ethernet, Serial
EL-QC-LW9	Base EL-QC & LoraWAN915, IO, Ethernet, Serial
EL-QC-R-C1	Base EL-QC & Radio 148-174Mhz, IO, Ethernet, Serial
EL-QC-R-C3	Base EL-QC & Radio 340-400Mhz, IO, Ethernet, Serial
EL-QC-R-C4	Base EL-QC & Radio 400-480Mhz, IO, Ethernet, Serial
EL-QC-R-C5	Base EL-QC & Radio 470-520Mhz, IO, Ethernet, Serial
EL-QC-R-U8	Base EL-QC & Radio 868Mhz, IO, Ethernet, Serial
EL-QC-R-U9	Base EL-QC & Radio 902-928Mhz FHSS, IO, Ethernet, Serial
EL-QC-CEL	Base EL-QC & Cellular LTE Bands, IO, Ethernet, Serial

Combination Model Order Codes		
EL-QC-R-Cx-LW8	Base EL-QC & Radio Cx & LoraWAN868, IO, Ethernet, Serial	
EL-QC-R-Cx-LW9	Base EL-QC & Radio Cx & LoraWAN915, IO, Ethernet, Serial	
Select Radio model, i.e. C1, C3, C4, C5, U8, U9	C1	148-174Mhz
	C3	340-400Mhz
	C4	400-480Mhz
	C5	470-520Mhz
	U8	868Mhz Fixed Freq
	U9	902-928Mhz FHSS
EL-QC-CEL-LW8	Base Model, Cellular LTE & LoraWAN868, IO, Ethernet, Serial	
EL-QC-CEL-LW9	Base Model, Cellular LTE & LoraWAN915, IO, Ethernet, Serial	

CONTACT

Australia
ELPRO Technologies
29 Lathe Street
Virginia QLD 4014
T +61 7 3352 8600
E sales@elprotech.com
W elprotech.com

USA
ELPRO Technologies Inc
2028 East Ben White Boulevard
#240-5656 Austin, TX 78741-6931
T +1 855 443 5776
E sales@elprotech.com
W elprotech.com

HOW TO ORDER

Simply send us an email at **sales@elprotech.com**, contact your local distributor, or phone **+61 7 3352 8600**